

Press information

Date: 22/06/2005

Increased flexibility when installing

“complli 400” by Jung Pumpen with new possibilities

Steinhagen – The “complli 400” sewage lifting system from Jung Pumpen, which is already well established in the market, is now even more flexible. With an enhanced model of the lifting system – which is available immediately – the wastewater specialist Jung Pumpen has extended their installation possibilities once again.

Flexible supply inlets for different installation situations

The horizontal DN 100 inlet – which is centrally attached – is still present as a clamping flange. In the new model, the height of this clamping flange can be adjusted and, depending on the inflow height, can be lowered from 250 to 180 mm in a short time period. As a result, it is possible to easily and directly connect the system to a floor standing WC.

In addition, besides the existing vertical inlet (Ø 50 mm), another horizontal inlet (Ø 50 mm) has been attached to the chamber side. If it is necessary to have a DN 100 inlet from above, the graduated ventilation connecting flange DN 70 can simply be extended to DN 100 and the ventilation pipe is connected to the added DN 70 connecting piece. With these arrangements, the unit offers the greatest flexibility possible and can be adapted to different installation situations. Furthermore, additional recessed grips on the front side of the unit make transporting the lifting system to the installation site easier.

Contact:
Company Press Office
Jung Pumpen GmbH
Bernd Schäfers-Maiwald
Industriestraße 4-6
33803 Steinhagen
Germany
Phone +49(0)52 0417- 320
Fax +49(0)52 0417- 133
bsm@jung-pumpen.de

Editorial Office:
Dr. Sälzer Pressedienst
Haverkamp 30
45289 Essen
Germany
Phone +49(0)201 89470-0
Fax +49(0)201 89470-22
www.drsoelzer-pressedienst.de

Press information

Ready to plug in and quiet running

The “compli 400” is distinguished by its optimal quietness during operation and the highest standard in chamber stability. The length-wise sealed, water-proof pipe inlet is still part of the standard package. The ready-to-plug-in system is therefore flood-safe and can also be used in rooms where there is a risk of flooding.

Reprint permitted. File copy requested.

*(This text is also available online from our text database
“www.drsoelzer-pressdienst.de”.)*

Contact:

Company Press Office
Jung Pumpen GmbH
Bernd Schäfers-Maiwald
Industriestraße 4-6
33803 Steinhagen
Germany
Phone +49(0)52 0417- 320
Fax +49(0)52 0417- 133
bsm@jung-pumpen.de

Editorial Office:

Dr. Sälzer Pressedienst
Haverkamp 30
45289 Essen
Germany
Phone +49(0)201 8 94 70 -0
Fax +49(0)201 8 94 70 -22
www.drsoelzer-pressdienst.de

Press information



Quiet running and reliable: The tried and tested “compli 400” lifting system from Jung Pumpen is available immediately as an enhanced model.

Photo: Jung Pumpen, Steinhagen

Date: 22/06/2005

(This image is also available in digital format: download at www.drsoelzer-pressdienst.de.)

Contact:
Company Press Office
Jung Pumpen GmbH
Bernd Schäfers-Maiwald
Industriestraße 4-6
33803 Steinhagen
Germany
Phone +49(0)52 0417- 320
Fax +49(0)52 0417- 133
bsm@jung-pumpen.de

Editorial Office:
Dr. Sälzer Pressedienst
Haverkamp 30
45289 Essen
Germany
Phone +49(0)201 8 94 70 -0
Fax +49(0)201 8 94 70 -22
www.drsoelzer-pressdienst.de

Press information



Flexible in application: A height-adjustable clamping flange with an integrated insertion restriction enables easy installation where functionality is assured. Thanks to additional inlets, the flexible system can be adapted to specific conditions during installation.

Photo: Jung Pumpen, Steinhagen

Date: 22/06/2005

(This image is also available in digital format: download at www.drsoelzer-pressdienst.de.)

Contact:
Company Press Office
Jung Pumpen GmbH
Bernd Schäfers-Maiwald
Industriestraße 4-6
33803 Steinhagen
Germany
Phone +49(0)52 0417-320
Fax +49(0)52 0417-133
bsm@jung-pumpen.de

Editorial Office:
Dr. Sälzer Pressedienst
Haverkamp 30
45289 Essen
Germany
Phone +49(0)201 89470-0
Fax +49(0)201 89470-22
www.drsoelzer-pressdienst.de